

## Section 1 - Product and Company Identification

### PSS 600 HEAVY DUTY PAINT REMOVER

---

**Product Identification:** PSS 600 HEAVY DUTY PAINT REMOVER

**Date of MSDS:** 06/12/1989 **Technical Review Date:** 09/05/1991

**FSC:** 8010 **NIIN:** LIIN: 00F018316

**Submitter:** F BT

**Status Code:** C

**MFN:** 01

**Article:** N

**Kit Part:** N

### Manufacturer's Information

**Manufacturer's Name:** ROCHESTER MIDLAND

**Post Office Box:** 1515

**Manufacturer's Address1:** N/K

**Manufacturer's Address2:** ROCHESTER, NY 14603-1515

**Manufacturer's Country:** NK

**General Information Telephone:** (716) 266-2250

**Emergency Telephone:** (716) 266-2283

**Emergency Telephone:** (716) 266-2283

**MSDS Preparer's Name:** N/P

**Proprietary:** N

**Reviewed:** Y

**Published:** Y

**CAGE:** 13091

**Special Project Code:** N

### Preparer Information

**Preparer's Name:** ROCHESTER MIDLAND CORPORATION

**Post Office Box:** 1515

**Preparer's Address1:** 333 HOLLENBECK STREET

**Preparer's Address2:** ROCHESTER, NY 14603-1515

**Preparer's CAGE:** 13091

**Assigned Individual:** N

### Contractor Information

**Contractor's Name:** ROCHESTER MIDLAND CORPORATION

**Post Office Box:** 1515

**Contractor's Address1:** 333 HOLLENBECK STREET

**Contractor's Address2:** ROCHESTER, NY 14603-1515

**Contractor's Telephone:** 716-336-2200

**Contractor's CAGE:** 13091

---

## Section 2 - Composition/Information on Ingredients

### PSS 600 HEAVY DUTY PAINT REMOVER

---

**Ingredient Name:** N-METHYL-2-PYRROLIDONE

**Ingredient CAS Number:** 872-50-4 **Ingredient CAS Code:** M

**RTECS Number:** UY5790000 **RTECS Code:** M

**=WT: =WT Code:**

**=Volume: =Volume Code:**

**>WT: >WT Code:**

**>Volume: >Volume Code:**

**<WT: <WT Code:**

**<Volume: <Volume Code:**

**% Low WT: % Low WT Code:**

**% High WT: % High WT Code:**

**% Low Volume: % Low Volume Code:**

**% High Volume: % High Volume Code:**

**% Text: >50%**

**% Environmental Weight:**

**Other REC Limits:** N/K

**OSHA PEL:** N/K **OSHA PEL Code:** M

**OSHA STEL:** OSHA STEL Code:

**ACGIH TLV:** N/K **ACGIH TLV Code:** M

**ACGIH STEL:** N/P **ACGIH STEL Code:**

**EPA Reporting Quantity:**

**DOT Reporting Quantity:**

**Ozone Depleting Chemical:** N

---

### Section 3 - Hazards Identification, Including Emergency Overview PSS 600 HEAVY DUTY PAINT REMOVER

---

**Health Hazards Acute & Chronic:** EYES: SEVERE IRRITATION, REDNESS, TEARING & POSSIBLE TISSUE DAMAGE. SKIN: IRRITATION, DERMATITIS & ABSORPTION. INHALATION: NAUSEA, HEADACHE, WEAKNESS & DIZZINESS. INGESTION: IRRITATION, NAUSEA & VOMIT ING.

**Signs & Symptoms of Overexposure:**

EYES: SEVERE IRRITATION, REDNESS, TEARING & POSSIBLE TISSUE DAMAGE. SKIN: IRRITATION, DERMATITIS & ABSORPTION. INHALATION: NAUSEA, HEADACHE, WEAKNESS & DIZZINESS. INGESTION: IRRITATION, NAUSEA & VOMIT ING.

**Medical Conditions Aggravated by Exposure:**

N/K

**LD50 LC50 Mixture:** N/K

**Route of Entry Indicators:**

**Inhalation:** YES

**Skin:** YES

**Ingestion:** YES

**Carcenogenicity Indicators**

**NTP:** NO

**IARC:** NO

**OSHA:** NO

**Carcinogenicity Explanation:** NONE

---

**Section 4 - First Aid Measures**  
**PSS 600 HEAVY DUTY PAINT REMOVER**

---

**First Aid:**

EYES: FLUSH W/PLENTY OF WATER FOR 15 MIN. SKIN: WASH W/SOAP & WATER.  
INHALATION: REMOVE TO FRESH AIR. AID IN BREATHING AS REQUIRED. INGESTION: IF CONSCIOUS, GIVE TWO GLASSES OF WATER & INDUCE VOMITING . OBTAIN MEDICAL ATTENTION IN ALL CASES.

---

**Section 5 - Fire Fighting Measures**  
**PSS 600 HEAVY DUTY PAINT REMOVER**

---

**Fire Fighting Procedures:**

WEAR POSITIVE PRESSURE SELF-CONTAINED BREATHING EQUIPMENT W/FULL FACE PROTECTION & PROTECTIVE CLOTHING. STAY UPWIND TO AVOID SMOKE & FUMES.

**Unusual Fire or Explosion Hazard:**

COMBUSTIBLE LIQUID.

**Extinguishing Media:**

WATER, FOAM, DRY CHEMICAL OR CO2

**Flash Point: Flash Point Text:** 200F

---

**Autoignition Temperature:**

**Autoignition Temperature Text:** N/A

**Lower Limit(s):** 1.3%

**Upper Limit(s):** 9.5%

---

**Section 6 - Accidental Release Measures**  
**PSS 600 HEAVY DUTY PAINT REMOVER**

---

**Spill Release Procedures:**

WEAR APPROPRIATE PROTECTIVE EQUIPMENT. REMOVE ALL IGNITION SOURCES & VENTILATE AREA. MOP OR SOAK UP & REMOVE OUTDOORS. DIKE TO CONTAIN SPILL. RECOVER ALL POSSIBLE. SOAK UP REMAINDER ON INERT MATERIAL & PLACE IN COVERED STEEL DRUMS FOR DISPOSAL.

---

**Section 7 - Handling and Storage**  
**PSS 600 HEAVY DUTY PAINT REMOVER**

---

**Handling and Storage Precautions:**

**Other Precautions:**

---

**Section 8 - Exposure Controls & Personal Protection**  
**PSS 600 HEAVY DUTY PAINT REMOVER**

---

**Respiratory Protection:**

USE NIOSH/MSHA APPROVED ORGANIC VAPOR RESPIRATOR IF >TLV/PEL.

**Ventilation:**

**GENERAL/LOCAL EXHAUST: TO MAINTAIN Protective Gloves:**

LATEX OR NEOPRENE

**Eye Protection:** CHEMICAL SPLASH GOGGLES

**Other Protective Equipment:** AS NEEDED

**Work Hygienic Practices:** REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.  
WASH THOROUGHLY AFTER HANDLING.

**Supplemental Health & Safety Information:** N/K

---

**Section 9 - Physical & Chemical Properties  
PSS 600 HEAVY DUTY PAINT REMOVER**

---

**HCC:**

**NRC/State License Number:**

**Net Property Weight for Ammo:**

**Boiling Point: Boiling Point Text:** >300F

**Melting/Freezing Point: Melting/Freezing Text:** N/K

**Decomposition Point: Decomposition Text:** N/K

**Vapor Pressure:** <1 **Vapor Density:** 3 MIN.

**Percent Volatile Organic Content:**

**Specific Gravity:** 1.055

**Volatile Organic Content Pounds per Gallon:**

**pH:** 6-7

**Volatile Organic Content Grams per Liter:**

**Viscosity:** N/P

**Evaporation Weight and Reference:** (N-BU AC = 1): <1

**Solubility in Water:** MISCIBLE

**Appearance and Odor:** VISCOUS, CLEAR COLORLESS LIQUID W/MILD AMINE ODOR

**Percent Volatiles by Volume:** 97-100

**Corrosion Rate:** N/K

---

**Section 10 - Stability & Reactivity Data  
PSS 600 HEAVY DUTY PAINT REMOVER**

---

**Stability Indicator:** YES

**Materials to Avoid:**

STRONG OXIDIZING, REDUCING AGENTS

**Stability Condition to Avoid:**

HIGH TEMPERATURES, OPEN FLAME & WELDING ARCS

**Hazardous Decomposition Products:**

CO & OXIDES OF NITROGEN

**Hazardous Polymerization Indicator:** NO

**Conditions to Avoid Polymerization:**

N/K

---

**Section 11 - Toxicological Information  
PSS 600 HEAVY DUTY PAINT REMOVER**

---

**Toxicological Information:**

N/P

---

**Section 12 - Ecological Information  
PSS 600 HEAVY DUTY PAINT REMOVER**

---

---

**Ecological Information:**N/P

---

**Section 13 - Disposal Considerations  
PSS 600 HEAVY DUTY PAINT REMOVER**

---

**Waste Disposal Methods:**DISPOSE OF IN ACCORDANCE W/LOCAL, STATE, & FEDERAL REGULATIONS. DON'T ALLOW MATERIAL TO ENTER SEWERS, DRAINS OR WATERWAYS.

---

**Section 14 - MSDS Transport Information  
PSS 600 HEAVY DUTY PAINT REMOVER**

---

**Transport Information:**N/P

---

**Section 15 - Regulatory Information  
PSS 600 HEAVY DUTY PAINT REMOVER**

---

**SARA Title III Information:**

N/P

**Federal Regulatory Information:**

N/P

**State Regulatory Information:**N/P

---

**Section 16 - Other Information  
PSS 600 HEAVY DUTY PAINT REMOVER**

---

**Other Information:**

N/P

**HAZCOM Label Information****Product Identification:** PSS 600 HEAVY DUTY PAINT REMOVER**CAGE:** 13091**Assigned Individual:** N**Company Name:** ROCHESTER MIDLAND CORPORATION**Company PO Box:** 1515**Company Street Address1:** 333 HOLLENBECK STREET**Company Street Address2:** ROCHESTER, NY 14603-1515 US**Health Emergency Telephone:** (716) 266-2283**Label Required Indicator:** Y**Date Label Reviewed:** 12/16/1998**Status Code:** C**Manufacturer's Label Number:****Date of Label:** 12/16/1998**Year Procured:** N/K**Organization Code:** G**Chronic Hazard Indicator:** N/P**Eye Protection Indicator:** N/P**Skin Protection Indicator:** N/P**Respiratory Protection Indicator:** N/P

**Signal Word:** N/P  
**Health Hazard:**  
**Contact Hazard:**  
**Fire Hazard:**  
**Reactivity Hazard:**